

# SPP-R210

2 inch mobile printer



Mobile POS  
/ Retail



Deliveries



Customer  
Service Center



Ticketing

# The industry's smallest and lightest



## Seamless Mobility

- Ideal for using smart devices including iPhone, iPad, and Android
- Versatile connectivity supported (802.11 b/g/n and more)
- 232g (0.51 lbs.) light weight, 20% slimmer and 25% smaller than SPP-R200II



## Field-work Optimization

- IP54 rated rugged design (with protective case)
- 1.2 m drop resistant
- Optional integrated card reader (MSR or MSR + SCR)
- Long-lasting battery life




## Outstanding Performance

- Fast printing speed of up to 90 mm/sec (receipt)
- Linerless label printing (optional)
- Low-temp (-15°C) printing




# SPP-R210

2 inch mobile printer



The World's No.1  
mobile printer manufacturer



Reported by Chunichisha

## Specifications

### Print Specifications

#### Print Method

Direct Thermal

#### Print Speed

Up to 90 mm/sec (Receipt)  
Up to 60 mm/sec (Linerless)  
12.5% pattern

#### Print Resolution

203 dpi

#### Print Width

Up to 48 mm

#### Sensor

Paper End: Reflective sensor  
Paper Cover Open: Two mechanical switches

### Media Characteristics

#### Media Type

Receipt, Linerless (optional)

#### Media Width

58 mm

#### Media Roll Diameter

Up to 30 mm

#### Media Thickness

0.07 ± 0.005 mm

#### Supply Method

Easy Paper Loading

### Physical Characteristics

#### Dimensions (W x L x D)

79.0 x 116.0 x 36.5 mm  
(3.11 x 4.57 x 1.44 inch)

#### Weight

Including MSR + battery: 232 g (0.51 lbs.)  
Paper: 34 g (0.07 lbs.)

#### Battery

7.4 V Li-ion, 1,200 mAh, Rechargeable  
Charging time: Up to 2.5 hrs

### Performance Characteristics

#### Memory

64 Mbit SDRAM, 32 Mbit FlashROM

#### Interface Options

USB V2.0 FS  
Bluetooth V3.0+EDR  
WLAN 802.11b/g/n  
(Infrastructure, Ad-hoc, Wi-Fi Direct)  
- WEP40/104, WPA1/2(PSK, EAP)

### Environment Characteristics

#### Temperature

Operating: -15 ~ 50°C (5 ~ 122°F)  
Storage: -30 ~ 70°C (-22 ~ 158°F)

#### Humidity

Operating: 10 ~ 80% RH

#### Sealing

IP54 (with protective case)

#### Drop Rate

1.2 m (4 ft.)

### Software

#### Emulation

BXL / POS

#### Driver

Windows Driver, OPOS Driver, JPOS Driver,  
Linux CUPS Driver

#### SDK

iOS SDK, Android SDK, Windows SDK

### Fonts / Graphics / Symbologies

#### Character Size

Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24

#### Characters Per Line

Font A: 32 Font B, C: 42

#### Character Sets

Alphanumeric: 95  
Expanded Graphics: 128 x 33 page  
International: 32

#### Graphics

Supporting user-defined fonts, graphics, formats,  
layouts, and logos

#### Barcode Symbologies

1D: Codabar, Code 39, Code 93, Code 128, EAN-8,  
EAN-13, ITF, UPC-A, UPC-E  
2D: Aztec, Data Matrix, MaxiCode, PDF417, QR code

### Accessories

#### Standard

Belt Clip, Battery Pack, Battery Charger, Power Cord,  
Paper

#### Optional

Belt Strap, Battery Pack\_V2 (with outer contacts),  
Single Battery Cradle, Quad Battery Charger,  
Wall Mount (for Quad Battery Charger),  
Vehicle Charger, USB Cable, Cleaning Pen

### Integrated Card Reader (optional)

#### MSR

3 Track, DUKPT (optional), T-DES Certified (optional)

#### SCR

EMV Level 1 certified, ISO7816,  
EMV2000 compliant, SAM 2 slots



BR-SRP-R210-EN-NOV15-V1

Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.

**BIXOLON®**

**BIXOLON Co., Ltd.**  
+82 (0) 31 218 5500  
sales@bixolon.com

**BIXOLON America Inc.**  
+1 858 764 4580  
sales@bixolonusa.com

**BIXOLON Europe GmbH**  
+49 211 68 78 54 0  
sales@bixolon.de

www.bixolon.com

