



CARE . TRUST . RESPONSIBILITY

RECEIPT PRINTER RP-700

MINI THERMAL PRINTER



RP-700 is the most efficient and elegant thermal receipt printer for retail and hospitality environment. Its high speed, compact size and support of both Front/Top receipt printout are suitable for any diversified environment, especially for stores that are looking for tidy table and space utilization. It is specially designed for flexible operation in both under or above counter operation mode.

Maximum protection against dust and liquid splashes can also be applied through its Front receipt printout mode, which are critical in extreme environment such as restaurants, bars, kitchens...etc.

RP-700 features in trendy outlook with glossy Black or White selections. Its Triple-Interface connectivity is capable of connecting any terminals hassle-free. With Apple certified "MFi", RP-700 can be paired with Apple iPad®, iPhone® and iPod Touch® hassle-free (optional connectivity).



Made for



iPod



iPhone



iPad

SPECIAL FEATURES

- 58-80mm paper printing width receipt Printer (2/3inch)
- Small footprint with dimension 127mm x 127mm x 134mm (LxWxH)
- Front paper load & Top paper load (BOTH)
- Resolution 203 dpi
- 250mm/sec high speed printing
- Multiple interfaces : ● USB+Serial+Ethernet ● USB+BT (Apple MFi certified)
- Selection of Glossy Black and Glossy White
- Energy Star certified
- JAVAPOS/OPOS/Linux support

RP-700

Item		RP-700
Printing	Method	Direct Thermal
	Paper Loading Scenario	Top and Front
	Speed	250mm/sec
	Width	Max 80mm
	Resolution	203DPI
Paper	Type	Thermal Paper
	Width	57.5/80/82.5mm
	Thickness	0.06mm~0.1mm
	Roll Diameter	Max. 83mm
	Roll Core Inner	12.5mm
Memory		RAM : 2MB, Flash : 4MB
Reliability	TPH Life	150km
	MCBF	70,000,000 Lines
Auto cutter		2,000,000 cuts
Sensor		Paper End, Cover Open, Black Mark, Paper Near End
Interface		* USB+Serial+Ethernet
		* USB+BT ("Mfi" certified)
Emulation		ESC/POS Command Compatible
Driver		Windows, MAC
		LinuxCUPS, OPOS, JavaPOS
Power	Type	External Adaptor
	AC	100~240Vac 50/60 Hz
	DC	24Vdc / 2.5A
Temperature		Operation 41°F ~ 113°F
		Storage -40°F ~ 140°F
Dimension		5 in x 5 in x 5.27 in (LxWxH)
Weight		3.88 lb
Color		Black / White
Certificate		FCC, CE, CB, 3C, MFi, Energy Star

*Specification is subject to change without prior notice

**PARTNER TECH USA INC.**

15320 Barranca Parkway Suite 150.

Irvine, CA 92618

TEL: +1-949-598-1888

sales@partnertechcorp.com